## Stephenville Fire Department Fire Prevention Division

1301 Pecan Hill Dr., Stephenville, Texas 76401 Phone: 254-918-1202 Fax: 254-918-1241 <a href="www.stephenvilletx.gov">www.stephenvilletx.gov</a>

UNDERGROUND FIR	E MAIN PERMIT			
PERMIT #: (OFFICIAL USE ONLY)	DATE:			
CONTRACTOR INFORMATION	PROJECT INFORMATION			
NAME:	NAME:			
ADDRESS:	ADDRESS:			
SCR #:	JOB VALUATIO	NI, ¢		
5011			CLIDMIT	TAT []
£ 3 (	(6) []	ADDITIONAI (DEVICES ADDE		
ONE)		RELOCATED) (6	,	D, OK
IS A SPRINKLER SYSTEM BEING INSTALLED? (SEPA	RATE PERMIT RE	QUIRED)	YES[]	NO[]
IS A STANDPIPE BEING INSTALLED?			YES []	NO[]
IS A FIRE PUMP BEING INSTALLED?			YES[]	NO [ ]
DOES THE UNDERGROUND FIRE MAIN CONNECT TO	THE FIRE SPRIN	KLER	YES[]	NO [ ]
RISER? (IF NO, THEN A SEPARATE PERMIT IS REQUII	RED FOR THE			
UNDERGROUND CONNECTION FROM END OF FIRE M	MAIN TO THE FIR	Œ		
SPRINKLER RISER.)				

Plans shall be submitted in PDF format to permits@stephenvilletx.gov

## **PERMIT FEES**

THERE IS NO FEE REQUIRED FOR THIS PERMIT IF THE PLANS ARE SUBMITTED WITH THE BUILDING/SITE PLANS AND/OR FIRE SPRINKLER PLANS. IF THE UNDERGROUND FIRE MAIN PERMIT IS BEING APPLIED FOR BY ITSELF THE FEES ARE AS BELOW:

Value up to \$6,250	\$210.00
VALUE \$6251 to \$250,000	\$310.00
VALUE \$250,001 to \$500,000	\$438.00
VALUE \$500,001 to \$1,000,000	\$567.00
VALUE \$1,000,001 to \$3,000,000	\$825.00
VALUE \$3,000,001 to \$6,000,000	\$1,236.00
VALUE \$6,000,001 and up	\$2,400.00 +
PRO-RATED FOR EACH \$1,000 above \$6,000,000	\$0.40

FEES INCLUDE ONE PERMIT, FIELD INSPECTIONS, AND PLAN REVIEW.

## Stephenville Fire Department Fire Prevention Division

1301 Pecan Hill Dr., Stephenville, Texas 76401 Phone: 254-918-1202 Fax: 254-918-1241 <a href="www.stephenvilletx.gov">www.stephenvilletx.gov</a>

REFER TO THE 2015 EDITION OF THE ICC CODES AND THE CITY OF STEPHENVILLE FIRE CODE AMENDMENTS. THE PLANNER SHALL MARK WITH AN "X" EACH LINE BELOW TO INDICATE THE INFORMATION IS INCLUDED WITH THE SUBMITTAL OR INDICATE WITH "N/A" IF NOT APPLICABLE. INCOMPLETE PERMIT APPLICATIONS WILL BE RETURNED WITHOUT A REVIEW.

## Plans shall be submitted in PDF format to permits@stephenvilletx.gov

PROVIDE THE FOLLOWING ON ALL PLAN SHEETS:

PRINT NAME: \_\_\_\_

PLANNER'S NAME, LICENSE NUMBER, AND ORIGINAL SIGNATURE OF RME-U  PROVIDE SCOPE OF WORK ON PLANS  ALL RELEVENT BUILDING INFORMATION IS PROVIDED (i.e. SITE LOCATION, SECTIONS, ELEVATION VIEWS. ECT.)  MINIMUM COVER DEPTH IS CLEARLY INDICATED ON PLANS  ALL OCCUPANT/OWNER INFORMATION IS PROVIDED (i.e. NAME, ADDRESS, PHONE NUMBERS)  ALL GRAPHICAL INFORMATION IS PROVIDED (i.e. SCALE, COMPASS, MATCHLINES, ect.)  BUILDING CODE/BUILDING PERMIT INFORMATION (i.e. OCCUPANCY CLASSIFICATION, CONSTRUCTION TYPE)  DETAILS OF FIRE HYDRANTS ARE PROVIDED (INCLUDING CONTROL VALVE FOR EACH HYDRANT)  MINIMUM PIPE SIZE OF 6-INCHES PROVIDED (HYDRAULIC CALCULATIONS INCLUDED TO PROVIDE ADEQUACY OF PIPE SMALLER THAN 6-INCHES)  FIRE DEPARTMENT CONNECTIONS ARE WIHTIN 50 FEET OF AN APPROVED FIRE LANE OR PUBLIC STREET AND WITHIN 300 FEET OF A FIRE HYDRANT  ALL WATER SUPPLY INFORMATION AND HYDRAULIC CALCULATIONS ARE PROVIDED, AS NECESSARY. (WATER FLOW TEST MUST BE CONDUCTED WITHIN 12 MONTHS OF PLAN SUBMITTAL DATE.)  PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL  REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TOF STEPHENVILLE CODES AND STANDARDS.  SIGNATURE:		COMPANY NAME, ADDRESS, PHONE NUMBER, AND STATE LICENSE NUMBER.
ALL RELEVENT BUILDING INFORMATION IS PROVIDED (i.e. SITE LOCATION, SECTIONS, ELEVATION VIEWS. ECT.)  MINIMUM COVER DEPTH IS CLEARLY INDICATED ON PLANS  ALL OCCUPANT/OWNER INFORMATION IS PROVIDED (i.e. NAME, ADDRESS, PHONE NUMBERS)  ALL GRAPHICAL INFORMATION IS PROVIDED (i.e. SCALE, COMPASS, MATCHLINES, ect.)  BUILDING CODE/BUILDING PERMIT INFORMATION (i.e. OCCUPANCY CLASSIFICATION, CONSTRUCTION TYPE)  DETAILS OF FIRE HYDRANTS ARE PROVIDED (INCLUDING CONTROL VALVE FOR EACH HYDRANT)  MINIMUM PIPE SIZE OF 6-INCHES PROVIDED (HYDRAULIC CALCULATIONS INCLUDED TO PROVIDE ADEQUACY OF PIPE SMALLER THAN 6-INCHES)  FIRE DEPARTMENT CONNECTIONS ARE WIHTIN 50 FEET OF AN APPROVED FIRE LANE OR PUBLIC STREET AND WITHIN 300 FEET OF A PIRE HYDRANT  ALL WATER SUPPLY INFORMATION AND HYDRAULIC CALCULATIONS ARE PROVIDED, AS NECESSARY. (WATER FLOW TEST MUST BE CONDUCTED WITHIN 12 MONTHS OF PLAN SUBMITTAL DATE.)  PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL  REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.		PLANNER'S NAME, LICENSE NUMBER, AND ORIGINAL SIGNATURE OF RME-U
MINIMUM COVER DEPTH IS CLEARLY INDICATED ON PLANS  ALL OCCUPANT/OWNER INFORMATION IS PROVIDED (i.e. NAME, ADDRESS, PHONE NUMBERS)  ALL GRAPHICAL INFORMATION IS PROVIDED (i.e. SCALE, COMPASS, MATCHLINES, ect.)  BUILDING CODE/BUILDING PERMIT INFORMATION (i.e. OCCUPANCY CLASSIFICATION, CONSTRUCTION TYPE)  DETAILS OF FIRE HYDRANTS ARE PROVIDED (INCLUDING CONTROL VALVE FOR EACH HYDRANT)  MINIMUM PIPE SIZE OF 6-INCHES PROVIDED (HYDRAULIC CALCULATIONS INCLUDED TO PROVIDE ADEQUACY OF PIPE SMALLER THAN 6-INCHES)  FIRE DEPARTMENT CONNECTIONS ARE WIHTIN 50 FEET OF AN APPROVED FIRE LANE OR PUBLIC STREET AND WITHIN 300 FEET OF A FIRE HYDRANT  ALL WATER SUPPLY INFORMATION AND HYDRAULIC CALCULATIONS ARE PROVIDED, AS NECESSARY. (WATER FLOW TEST MUST BE CONDUCTED WITHIN 12 MONTHS OF PLAN SUBMITTAL DATE.)  PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL  REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.		PROVIDE SCOPE OF WORK ON PLANS
ALL OCCUPANT/OWNER INFORMATION IS PROVIDED (i.e. NAME, ADDRESS, PHONE NUMBERS)  ALL GRAPHICAL INFORMATION IS PROVIDED (i.e. SCALE, COMPASS, MATCHLINES, ect.)  BUILDING CODE/BUILDING PERMIT INFORMATION (i.e. OCCUPANCY CLASSIFICATION, CONSTRUCTION TYPE)  DETAILS OF FIRE HYDRANTS ARE PROVIDED (INCLUDING CONTROL VALVE FOR EACH HYDRANT)  MINIMUM PIPE SIZE OF 6-INCHES PROVIDED (HYDRAULIC CALCULATIONS INCLUDED TO PROVIDE ADEQUACY OF PIPE SMALLER THAN 6-INCHES)  FIRE DEPARTMENT CONNECTIONS ARE WIHTIN 50 FEET OF AN APPROVED FIRE LANE OR PUBLIC STREET AND WITHIN 300 FEET OF A FIRE HYDRANT  ALL WATER SUPPLY INFORMATION AND HYDRAULIC CALCULATIONS ARE PROVIDED, AS NECESSARY. (WATER FLOW TEST MUST BE CONDUCTED WITHIN 12 MONTHS OF PLAN SUBMITTAL DATE.)  PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL  REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TOP STEPHENVILLE CODES AND STANDARDS.		ALL RELEVENT BUILDING INFORMATION IS PROVIDED (i.e. SITE LOCATION, SECTIONS, ELEVATION VIEWS. ECT.)
ALL GRAPHICAL INFORMATION IS PROVIDED (i.e. SCALE, COMPASS, MATCHLINES, ect.)  BUILDING CODE/BUILDING PERMIT INFORMATION (i.e. OCCUPANCY CLASSIFICATION, CONSTRUCTION TYPE)  DETAILS OF FIRE HYDRANTS ARE PROVIDED (INCLUDING CONTROL VALVE FOR EACH HYDRANT)  MINIMUM PIPE SIZE OF 6-INCHES PROVIDED (HYDRAULIC CALCULATIONS INCLUDED TO PROVIDE ADEQUACY OF PIPE SMALLER THAN 6-INCHES)  FIRE DEPARTMENT CONNECTIONS ARE WIHTIN 50 FEET OF AN APPROVED FIRE LANE OR PUBLIC STREET AND WITHIN 300 FEET OF A FIRE HYDRANT  ALL WATER SUPPLY INFORMATION AND HYDRAULIC CALCULATIONS ARE PROVIDED, AS NECESSARY. (WATER FLOW TEST MUST BE CONDUCTED WITHIN 12 MONTHS OF PLAN SUBMITTAL DATE.)  PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL  REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.  SIGNATURE:  SCR #		MINIMUM COVER DEPTH IS CLEARLY INDICATED ON PLANS
BUILDING CODE/BUILDING PERMIT INFORMATION (i.e. OCCUPANCY CLASSIFICATION, CONSTRUCTION TYPE)  DETAILS OF FIRE HYDRANTS ARE PROVIDED (INCLUDING CONTROL VALVE FOR EACH HYDRANT)  MINIMUM PIPE SIZE OF 6-INCHES PROVIDED (HYDRAULIC CALCULATIONS INCLUDED TO PROVIDE ADEQUACY OF PIPE SMALLER THAN 6-INCHES)  FIRE DEPARTMENT CONNECTIONS ARE WIHTIN 50 FEET OF AN APPROVED FIRE LANE OR PUBLIC STREET AND WITHIN 300 FEET OF A FIRE HYDRANT  ALL WATER SUPPLY INFORMATION AND HYDRAULIC CALCULATIONS ARE PROVIDED, AS NECESSARY. (WATER FLOW TEST MUST BE CONDUCTED WITHIN 12 MONTHS OF PLAN SUBMITTAL DATE.)  PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL  REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.		ALL OCCUPANT/OWNER INFORMATION IS PROVIDED (i.e. NAME, ADDRESS, PHONE NUMBERS)
DETAILS OF FIRE HYDRANTS ARE PROVIDED (INCLUDING CONTROL VALVE FOR EACH HYDRANT)  MINIMUM PIPE SIZE OF 6-INCHES PROVIDED (HYDRAULIC CALCULATIONS INCLUDED TO PROVIDE ADEQUACY OF PIPE SMALLER THAN 6-INCHES)  FIRE DEPARTMENT CONNECTIONS ARE WIHTIN 50 FEET OF AN APPROVED FIRE LANE OR PUBLIC STREET AND WITHIN 300 FEET OF A FIRE HYDRANT  ALL WATER SUPPLY INFORMATION AND HYDRAULIC CALCULATIONS ARE PROVIDED, AS NECESSARY. (WATER FLOW TEST MUST BE CONDUCTED WITHIN 12 MONTHS OF PLAN SUBMITTAL DATE.)  PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL  REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.  SIGNATURE:  SCR #		ALL GRAPHICAL INFORMATION IS PROVIDED (i.e. SCALE, COMPASS, MATCHLINES, ect.)
MINIMUM PIPE SIZE OF 6-INCHES PROVIDED (HYDRAULIC CALCULATIONS INCLUDED TO PROVIDE ADEQUACY OF PIPE SMALLER THAN 6-INCHES)  FIRE DEPARTMENT CONNECTIONS ARE WIHTIN 50 FEET OF AN APPROVED FIRE LANE OR PUBLIC STREET AND WITHIN 300 FEET OF A FIRE HYDRANT  ALL WATER SUPPLY INFORMATION AND HYDRAULIC CALCULATIONS ARE PROVIDED, AS NECESSARY. (WATER FLOW TEST MUST BE CONDUCTED WITHIN 12 MONTHS OF PLAN SUBMITTAL DATE.)  PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL  REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.  SIGNATURE:		BUILDING CODE/BUILDING PERMIT INFORMATION (i.e. OCCUPANCY CLASSIFICATION, CONSTRUCTION TYPE)
PIPE SMALLER THAN 6-INCHES)  FIRE DEPARTMENT CONNECTIONS ARE WIHTIN 50 FEET OF AN APPROVED FIRE LANE OR PUBLIC STREET AND WITHIN 300 FEET OF A FIRE HYDRANT  ALL WATER SUPPLY INFORMATION AND HYDRAULIC CALCULATIONS ARE PROVIDED, AS NECESSARY. (WATER FLOW TEST MUST BE CONDUCTED WITHIN 12 MONTHS OF PLAN SUBMITTAL DATE.)  PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL  REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.  SIGNATURE:  SCR #		DETAILS OF FIRE HYDRANTS ARE PROVIDED (INCLUDING CONTROL VALVE FOR EACH HYDRANT)
WITHIN 300 FEET OF A FIRE HYDRANT  ALL WATER SUPPLY INFORMATION AND HYDRAULIC CALCULATIONS ARE PROVIDED, AS NECESSARY. (WATER FLOW TEST MUST BE CONDUCTED WITHIN 12 MONTHS OF PLAN SUBMITTAL DATE.)  PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL  REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.  SIGNATURE: SCR #		
FLOW TEST MUST BE CONDUCTED WITHIN 12 MONTHS OF PLAN SUBMITTAL DATE.)  PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL  REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.  SIGNATURE: SCR #		
REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS  LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.  SIGNATURE: SCR #		
LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS  HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.  SIGNATURE: SCR #		PIPE EMBEDMENT MATERIAL IS SAND OR OTHER APPROVED MATERIAL
HEREBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY TO STEPHENVILLE CODES AND STANDARDS.  SIGNATURE: SCR #		REQUIRED BACKFLOW PREVENTION DEVICES AND TYPE OF CONTROL VALVE MONITORING DETAILED ON PLANS
OF STEPHENVILLE CODES AND STANDARDS.  SIGNATURE: SCR #		LOCATIONS OF ALL THRUST BLOCKS SHOWN ON PLANS
OF STEPHENVILLE CODES AND STANDARDS.  SIGNATURE: SCR #	HEI	REBY CERTIFY THAT THIS SUBMITTAL CONTAINS THE ABOVE INFORMATION AS REQUIRED BY T
		·
<del></del>	SIGN	JATURE: SCR #
		· · · · · · · · · · · · · · · · · · ·

TELEPHONE #